



## Extension Module GBX20

The GBX20 is an Extension Module that adds functionality, versatility and flexibility to Grandstream's GRP2615 Carrier-Grade IP Phone and GXV3350 IP Video Phone. It features a 272x480 LCD display that offers up to 40 contacts per module with support for up to 160 contacts by using 4 modules. The GBX20 supports a wide-range of advanced call features including BLF, call park/pick-up, speed-dial, presence, intercom, voice conferencing transfer/forward and much more. An ideal solution for businesses and receptionists managing high call volumes, the GBX20 ensures maximum productivity by efficiently monitoring and dispatching incoming calls.

<b>Lines</b>	20 per page (each module contains 2 pages, for up to 40 lines per module Up to 160 with 4 daisy-chained modules)
<b>Compatible Grandstream IP Phones</b>	GRP2615 and GXV3350
<b>Graphic Display</b>	4.3 inch (272x480) TFT color LCD
<b>Feature Support</b>	Local GUI: Multiple line/call appearances
<b>Power</b>	A single GBX20 can be powered by host phone (GRP2615 or GXV3350); when 2 or more GBX20 are connected the included 12V/1A PSU will power the GBX20s.
<b>Firmware Upgrades</b>	GBX20 firmware is upgraded by direct network download through host phone (GRP2615 or GXV3350)'s network connection and firmware upgrade setup.
<b>Physical</b>	Dimension: 210mm*124mm*33.5mm; Unit weight: 360g; Package weight:700g
<b>Temperature and Humidity</b>	Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing
<b>Package Content</b>	GBX20 Extension Board, base stand, Extension Board Connector Plate, Screws, USB cable, Quick Installation Guide, 12V/1A Power Adapter.
<b>Compliance</b>	FCC: Part 15 Class B IC: ICES-003 CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 62368-1 RCM: AS/NZS CISPR32; AS/NZS 62368.1