



Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Rated power in W	2700 W
Rated power in VA	3000 VA
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers 2 IEC 320 C19
Output voltage	230 V
Output voltage	208 V 220 V 240 V
Input voltage	208 V 230 V
Plug standard	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
Number of rack unit	4U
Cable length	1.83 m
Number of cables	1

General

Number of power module	2400
Number of power module filled slots	0
Number of power module free slots	0
Number of tare power	41 W

Product web sub-family	Extended run
Redundant	No
Provided equipment	CD with software Documentation CD Smart UPS signalling RS-232 cable User manual USB cable Rack mounting brackets

Physical

Mounting location	Front
Mounting mode	Rack-mounted
Mounting preference	Lower
Depth	48.3 cm
Height	43.2 cm
Product weight	38.64 kg
Width	17.8 cm
Two post mountable	1
USB compatible	Yes
Colour	Black

Input

Input voltage	220 V 240 V
Input voltage limits	140...280 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Crest factor	3 : 1
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE EAC IRAM RCM TISI VDE
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Acoustic level	55 dBA
Heat dissipation	184 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %

Storage Relative Humidity	0...95 %
---------------------------	----------

Batteries & Runtime

Battery type	Lead-acid battery
Extended runtime	1
Liquid value	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Battery power in VAH	738 VAh runtime
Battery charger power	245 W rated
Battery option	SMX120BP 1 2214 VAh SMX120BP 2 3690 VAh SMX120BP 3 5166 VAh SMX120BP 4 6642 VAh SMX120BP 6 9594 VAh SMX120BP 8 12546 VAh SMX120BP 10 15498 VAh

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	LED status display with on line : on battery : replace battery and overload indicators Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1

Surge Protection and Filtering

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	47.73 kg
Package 1 Height	33 cm
Package 1 width	58.6 cm
Package 1 Length	63.3 cm
Number of Units in Package 3	6
Package 3 Weight	388.69 kg
Package 3 Height	110.49 cm
Package 3 width	121.92 cm
Package 3 Length	78.74 cm
Pallet unit layers	2
Pallet layers	4

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--