

# CooVox-U20 IP Phone System

for Small and Medium Businesses



## First Mini Mobile PBX

### NO USER LICENSE FEES

All standard PBX features

Many Advanced PBX features


Smart phone integration

### INCREASED SECURITY

Enhanced Security policies

Firewall

Intrusion Detection



CooVox-U20 IP Phone system is the second generation of Mini IP Phone system released from ZYCOO, meanwhile it's the first Mobile IP Phone system with the ability to use the GSM or UMTS (3G) module to connect to the mobile network for data transport.

CooVox-U20 is a next-generation smart IP PBX system designed and optimized for today's business telecommunication needs. CooVox-U20 is an affordable, scalable, interoperable, secure and reliable solution which not only provides traditional PBX functions such as automated attendant and voicemail, but also many advanced features including remote extensions, remote office connection, conference bridge, call recording, call detail records (CDR), automatic call distribution (ACD), unified messaging (voice mail to email), and many more features.

### Benefits & Features:

- 30 IP Phone registrations/Extensions and around 10 concurrent call legs for cost-effective communication.
- Fax to Email/Email to Fax.
- Voicemail to Email.
- Paging and Intercom function strengthens the working efficiency.
- Monitor and Whisper
- HD voice codec G.722 for perfect voice quality.
- Strong security features protect your system from hacking.

### Telephony Configuration:

Model	FXO	FXS
CooVox-U20-A202	2	0
CooVox-U20-A211	1	1

GSM or UMTS(3G) is optional for configuration.

## System Specifications

### Call Features

Call Back  
Call Forward  
Call Hold  
Call Paging and Intercom  
Call Park  
Call Pickup  
Call Queue  
Call Recording  
Call Routing  
Blind Transfer  
Attend Transfer  
Call Waiting  
Caller ID  
Dial by Name  
Music on Hold / Transfer  
Three-Way Conference  
Video Calls

### PBX Features

Black List  
BLF (Busy Lamp Field)  
CDR (Call Detailed Record)  
Conference Room (3 rooms)  
Call Monitoring  
DID (Direct Inward Dialing Number)  
DISA (Direct Inward System Access)  
Distinctive Ringtone  
DND  
DNIS  
Feature Codes  
Flash Operation Panel  
Follow Me  
IP Phone Provisioning  
IVR (Interactive Voice Responses)  
Mobility Extension  
Multi-Language Prompt  
Multi-Language GUI  
One Touch Record  
Phone Book  
Phone Provisioning  
Pin Sets  
Record Files Download  
Ringgroup  
SIP Register with UDP/TCP/TLS  
SIP Trunk  
Skype for SIP  
Smart DID  
Speed Dial  
Spy  
S RTP  
System Log  
T.38 FAX(Pass-through)  
Time based rule  
Virtual FAX  
Voicemail & Voicemail to Email

### System Capacity

10 Concurrent Call Legs  
Up to 30 IP Phone Registers/Extensions  
Recording(GSM/ default): 21,000 mins;  
Wav: 3000 mins  
Voicemail(GSM/ default): 21,000 mins  
Wav: 3000 mins

### Codec & Protocol

Audio Codec: G.722/ G.711-Ulaw/ G.711-  
Alaw/ G.726/ G.729/ GSM/ SPEEX  
Video Codec: H.261/ H.263 / H.263+ / H.264  
Protocol: SIP (RFC3261) , IAX2  
DTMF: RFC2833, SIP INFO, In-band

### Network Features

DDNS Client  
DHCP Server  
IEEE802.1Q of VLAN  
IP Assignment (PPPoE / DHCP / Static)  
IPv4 / IPv6  
SNMP v1/v2  
Static Route Table by manually  
Trouble Shooting (Ping, Traceroute)  
VPN Client  
(Support N2N / L2TP/PPTP/OPENVPN)  
VPN Server(PPTP/L2TP/OPENVPN Server 10)

### Security Features

Refuse SIP Register DoS  
Refuse Abort Invite Dos  
Refuse SSH Login DoS  
FireWall  
S RTP

### Log

SSH Log  
System Log  
Web Access Log  
Asterisk Debug Log  
Phone Register Log

### Hardware Interface

1 Reset Button  
1 Power Interface  
1 Ethernet Interface  
2 Analog Ports (FXO/FXS)  
1 GSM Antenna Interface  
1 UMTS Interface for 3G Data (onboard)  
LED indication

### Hardware Specifications

CPU: DualCore 500Mhz DSP  
SDRAM: 128MB DDR2  
Storage: 4GB (Default SD Card )  
Power Supply:  
Input: 100 ~ 240 Vac  
Output: DC 12V 1.0 A

### Environment

Working Temperature -10 °C -45 °C  
Storage Temperature: -30 °C -65 °C  
Humidity: 10-80% No Dew

### Packaging

Dimension:155 × 295 × 65 mm  
Weight: 0.8kg

